

**ENGINES**

Model	Cylinders	Continuous Duty	
		HP	RPM
K6	1	2.7-4.8 HP	400-800 RPM
C-46	1	5-9 HP	450-800 RPM
C-66	1	7-13 HP	350-700 RPM
C-96	1	11-19 HP	300-600 RPM
C-101	1	19-24.5 HP	400-800 RPM
C-106	1	17-32 HP	300-800 RPM
C-255	2	32-55 HP	400-750 RPM
L-795	2	35-65 HP	300-600 RPM
A-32	3	17-24.5 HP	1000-1200 RPM *
A-42 (VR260)	4	24-47 HP	1000-1800 RPM
A-54 (VR330)	6	26-68 HP	900-1800 RPM
A-62 (VR380)	6	40-80 HP	900-1800 RPM
A-62TA (VR380TA)	6	64-115 HP	1000-1800 RPM
A-90	6	57-109 HP	900-1800 RPM
A-90TA	6	73-151 HP	1000-1800 RPM
A-160	6	184-215 HP	1200-1800 RPM

\*Steady state operation only

**Gensets 1-2 Cylinder**

Model	kW rating	Engine RPM	Alternator RPM
C-46 AC	5 kW	700	1800
C-46 DC	5 kW	700	1800
C-66 AC	7.5 kW	600	1800
C-96 AC	13.5 kW	600	1800
C-106 AC	22 kW	700	1800

**Gensets 4-6 Cylinder**

Model	Prime Power Ratings		Standby Power Ratings	
	1,800 RPM	1,500 RPM	1,800 RPM	1,500 RPM
A-42 (VR260)	28 kW	23 kW	30 kW	25 kW
A-54 (VR330)	43 kW	36 kW	48 kW	39 kW
A-62 (VR380)	50 kW	42 kW	55 kW	45 kW
A-62TA (VR380TA)	75 kW	63 kW	83 kW	69 kW
A-90	75 kW	63 kW	93 kW	77 kW
A-90TA	100 kW	95 kW	109 kW	105 kW
A-160	147 kW	128 kW	161 kW	142 kW

2301 East Independence • Tulsa, Oklahoma 74110 • toll free 800 331-3662 • local (918) 583-5711

**(800) 331-3662 • www.ArrowEngine.com**



Quality Products...Engineered to Last

# PRODUCT COMPARISON



## VRC Compressor

two-throw separable reciprocating gas compressor

**DOUBLE ACTING CYLINDERS**

Bore In	MAWP PSIG
2.5	1500
3.0	1500
3.5	1000
4.0	1000
4.5	750
5.0	750
5.5	500
6.0	500
6.5	400
7.0	400
7.5	200
8.0	200

**STEEPLE CYLINDERS**

Bore, In SACE x SAHE	MAWP, PSIG CE/HE
3.5 X 2.25	1000/2250
4.0 X 2.25	1000/2250
4.5 X 2.50	750/2250
4.5 X 3.0	750/1500
4.5 X 3.5	750/1500
5.0 X 2.50	750/2250
5.0 X 3.0	750/1500
5.0 X 3.5	750/1500
5.5 X 3.0	500/1500
5.5 X 3.5	500/1500
6.0 X 3.0	500 /1500
6.0 X 3.5	500/1500
6.5 X 4.0	400/1000
6.5 X 4.5	400/1000
7.0 X 4.0	400/1000
7.0 X 4.5	400/1000



## Gas Products

- ASME Code Vessels
- Volume Tanks
- Vertical & Horizontal Separators
- Meter Runs
- Suction Scrubbers
- Coalescers
- Skids

## Chemical Pumps

Model	Operation	Max Discharge	Max Discharge / Day
10 Series	Beam	1,500-3,000 PSI	12-184 Quarts
12 Series	Pneumatic	1,500-5,500 PSI	50-240 Quarts
430 Series	Electric	600-3,000 PSI	1-640 Quarts
500 Series	Pneumatic	2,000-12,000 PSI	64-2,400 Quarts
510 Series	Pneumatic	100-6,000 PSI	9-128 Quarts
1200 Series	Solar	1,200 PSI	20-40 Quarts

## Autostart

- Automatic on/off cycle timing
- Continuous monitoring
- Automatic engine shutdown
- Oil circuit integrity
- Selectable speed ranges
- Automatic start-up sequence
- Start attempt counter

## AutoStart NS-2

- Automatic off/on cycle timing
- Different cycles each day of the week
- Continuous monitoring of critical engine operating parameters
- Automatic shutdown
- Simple to install 8-wire system
- Built in tachometer, hour meter, and battery voltage meter
- Automation may be set to real time, interval timing, or manual mode